

Industry Leader in RO Expertise and Membrane Applications since 1983™

AM-22 Product Specifications

Thin Film Composite RO Membrane Alkaline Cleaner

Especially Formulated for Removing Oil, Grease, Biological Matter, Natural Organic Foulants, Calcium Sulfate, and Grime

AM-22 is a non-chlorinated alkaline product formulated for the requirements of TFC type RO membranes. It has good soil suspending characteristics, and is designed to function at low temperatures up to 120°F. AM-22 should be used under minimum pressure and maximum flow condition. It contains no surfactants, therefore foam problems are avoided.

SPECIFICATIONS:	
Appearance and Odor:	White, alkaline powder with no distinct odor.
• pH (2% solution):	10 to 12
Solubility in Water:	Completely
Foam Level:	None
• Cloud Point:	None
• Freezing Point:	None
Risibility:	Excellent
• Stability:	Stable when stored in a closed container under cool, dry conditions.



Warning: Prevent contact with skin, eyes, and avoid contamination of clothing. Avoid inhaling dust. Destructive to tissue contacted and produces severe burns. Inhalation of dust, mist, or spray may cause damage to the upper respiratory tract and even to the lung tissue. If contact with skin occurs, immediately wash contaminated areas with plenty of water for 15 minutes. Launder clothing before reuse. If inhaled, remove person to fresh air. If ingested, give large quantities of water. If vomiting occurs spontaneously, keep airway clear. In case of eye contact, flush immediately with large amounts of water for at least 15 minutes, holding eyelids apart to ensure flushing of the entire surface. Seek medical attention immediately. Use NIOSH/MSHA approved respirators where dust, mist, or spray may be generated, natural or butyl rubber gloves, face shield and goggles, coveralls closed to the neck, and chemically resistant shoes. Contain and clean up immediately. Neutralize remaining traces of material with any dilute inorganic acid or lime. Dispose of waste material according to federal, state, and local regulations. Avoid contact with water, strong acids, leather or wool, and reactive metals.

Applied Membranes, Inc. assumes no liability for results obtained or damages incurred through the improper application of the above information and data.







